


MATERIAL SAFETY DATA



Baton Rouge Industries, Inc.
 5319 Groom Road • P.O. Box 26
 Baker, Louisiana 70714
 1-800-232-0334 • 225-775-3362
 FX 225-775-3498
BatonRougeIndustries.com

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

IDENTITY INFORMATION						
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special- -			HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B			
Manufactured By: Baton Rouge Industries Inc. Address: P.O. Box 26 5319 Groom Rd. Address: Baker, La. 70714			DOT Hazard Classification: Flammable Liquid 3 Identity: L-600 EXCELUBE FUEL & OIL CONDITIONER			
Phone: 225-775-3362			MSDS Number: L-600 Supersedes All Prior			
Emergency Response Number: 800-232-0334			Date Prepared: 10-01-09 Prepared By: David Beasley			
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA			Information Calls: 800-232-0334			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
BUTYL HYDRATE		78-92-2	Yes	150	100	d
CRESOL		1319-77-3	Yes	5	5	d
PETROLEUM DISTILLATE		8002-05-9	No	5mg/M3	5mg/M3	d
DOT UN 1993 PG 3, Contains aliphatic Alcohol						
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: 120°F			Specific Gravity (H2O=1): 0.89			
Vapor Pressure: PSIG @ 70°F (Aerosols): N/A			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): 200			
Vapor Density (Air = 1): 4			Evaporation Rate (BUAC = 1): 2			
Solubility in Water: Negligible			Water Reactive: Neg.			
Appearance and Odor: Clear green liquid with characteristic odor.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME		Auto Ignition Temperature		Flammability Limits in Air by % in Volume:		
PROJECTION TEST (aerosols) N/A		N/D		% LEL: N/D % UEL: N/D		
FLASH POINT AND METHOD USED (non-aerosols): 83°F TCC			EXTINGUISHER MEDIA: Dry chemical (preferred), carbon dioxide, water fog.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Slight when exposed to heat or flame. Combustible at high temperatures.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE			HAZARDOUS POLYMERIZATION <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Strong oxidizers.			Conditions to Avoid: Oxidizing atmospheres, heat, flames, sparks.			
Hazardous Decomposition Products: Oxides of carbon.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input checked="" type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE <input type="checkbox"/> NOT HAZARDOUS						
ACUTE EFFECTS:						
Inhalation: Headache, nausea, incoordination, drowsiness.						
Eye Contact: Irritant, may cause chemical burn.			Skin Contact: Irritant, may cause chemical burn.			
Ingestion: May cause vomiting, nausea, diarrhea. May get systemic poisoning.						
CHRONIC EFFECTS: None noted.						
Medical Conditions Generally Aggravated by Exposure: None noted other than irritant.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Wash with large amounts of water. If irritation persists, call a physician.						
Skin Contact: Remove contaminated clothing. Wash with soap and water.						
Inhalation: Remove to fresh air.						
Ingestion: DO NOT INDUCE VOMITING. Give 3-4 glasses of water. Seek medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): NIOSH / MSA self-contained breathing apparatus in confined areas.						
Protective Gloves: Neoprene or plastic.			Eye Protection: Splash goggles or safety glasses.			
Ventilation Requirements: None required in excess to normal ventilation.						
Other Protective Clothing & Equipment: Oil resistant apron.						
Hygienic Work Practices: Do not work in oil soaked clothing. Wash after handling.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Stop flow, dike spill, eliminate all ignition sources, absorb on inert material and scrape up.						
Waste Disposal Methods: Dispose of in accordance with local, state and federal regulations.						
Precautions To Be Taken In Handling & Storage: Avoid prolonged exposure to mist and vapors. Avoid flames, sparks and hot surfaces. Keep containers closed. Shelf life one year.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Remove ignition sources.						