



L-609 HYDRAULIC OIL (TURBINE GRADE)

Revised 10-1-09

DESCRIPTION

L-609 Hydraulic Oil (Turbine Grade) is a superior quality turbine grade hydraulic oil blended from hydrotreated, virgin 100% paraffin base oils and fortified with the most advanced additives available today to assure long equipment life under heavy duty applications.

L-609 Hydraulic Oil (Turbine Grade) meets and/or exceeds all major hydraulic equipment manufacturer requirements, including Dennison, Sperry Vickers, and Cincinnati Milicron.

COMPOSITION

L-609 Hydraulic Oil (Turbine Grade) is specially formulated with high viscosity index base stocks and superior additives to give excellent temperature and oxidation stability and provide maximum protection of systems from wear & corrosion damage. In addition, L-609 Hydraulic Oil (Turbine Grade) is fortified with the following additives for optimum performance.

Rust & Oxidation Inhibitors
Heat Dissipants
Viscosity Index Improvers

Anti-Wear Additives
Demulsifiers
Stabilizing Additives

Anti-Foam Additives
Seal Conditioners
Friction Modifiers

APPLICATIONS

Forklifts/Draglines/Cranes/Shovels/Dump Trucks/Balers/Hydraulic presses/Hydraulic elevators/Cherry pickers/Hydraulic lifts/Hoists/Winch/Hydraulic jacks/Injection molding presses/Tractors and construction equipment.

<u>SPECIFICATIONS</u>				
ISO Grade	32	68	100	150
SAE Grade	10	20	30	40
Viscosity @ 100 °F, SUS	170	324	615	750
Viscosity @ 210 °F, SUS	43/47	53/58	65/69	75/79
Viscosity Index	95	95	95	95
Flash point, °F	400	400	415	430
Pour Point, °F	0	+5	+10	+10
Rust Test, D-665A & B	Pass	Pass	Pass	Pass
Anti-Wear Treated	Yes	Yes	Yes	Yes
Demulsibility Test D-1401	Pass	Pass	Pass	Pass

**For Product Information Sheets and Material Safety Data Sheets,
Please visit our website: BatonRougeIndustries.com**