



L-609-B HYDRA-CLEAR HYDRAULIC OIL (FOOD GRADE)

Revised 10-1-09

DESCRIPTION

L-609-B Hydra-Clear Hydraulic Oil (Food Grade) is a superior lubricant formulated with hydrotreated, food grade, base oils to provide maximum lubrication protection for hydraulic pumps and components in high performance applications as well as environmentally sensitive areas. These superior grade oils are further enhanced with the most advanced additives for optimum lubrication protection for today's high demand equipment. L-609-B also meets USDA H-1 specifications for applications where incidental contact with food may occur.

L-609-B Hydra-Clear Hydraulic Oil (Food Grade) is an ashless formulation and passes the stringent, acute aquatic toxicity (LC-50) test and is inherently biodegradable & environmentally friendly.

COMPOSITION

Rust & Oxidation Inhibitors
 Heat Dissipants
 Viscosity Index Improvers

Anti-Wear Additives
 Demulsifiers

Anti-Foam Additives
 Stabilizers

APPLICATIONS

L-609-B Hydra-Clear Hydraulic Oil (Food Grade) meets and/or exceeds all major hydraulic equipment manufacturer requirements, including Dennison, Sperry Vickers, and Cincinnati Milicron, while providing an additional level of safety in case of leaks or incidental discharge to the environment.

L-609-B Hydra-Clear Hydraulic Oil (Food Grade) is formulated for mobile and stationary hydraulic vane-piston, and gear-type pumps and hydraulic systems operating where pressures may exceed 5000 psi.

<u>SPECIFICATIONS</u>	
ISO Grade	68
SAE Grade	20
Viscosity @ 40 °C, cSt	65.1
Viscosity @ 100 °C, cSt	8.4
Viscosity @ 100 °F, SUS	308
Viscosity @ 210 °F, SUS	53.4
Viscosity Index	95
Flash point, °F	520
Pour Point, °F	-20
ASTM Rust Test	Pass

**For Product Information Sheets and Material Safety Data Sheets,
 Please visit our website: BatonRougeIndustries.com**