



## **L-609-AL ANTI-LEAK HYDRAULIC OIL**

Revised 10-1-09

### **DESCRIPTION**

L-609-AL Anti-Leak Hydraulic Oil is a superior quality, turbine grade hydraulic oil blended from hydrotreated, virgin, 100% paraffin base oils and formulated for heavy duty applications where excessive leaks are a serious problem. L-609-AL Anti-Leak Hydraulic Oil meets and/or exceeds all major hydraulic equipment manufacturer requirements, including Dennison, Sperry Vickers, and Cincinnati Milicron.

### **COMPOSITION**

L-609-AL Anti-Leak Hydraulic Oil is specially formulated with high viscosity index base stocks and superior additives to give excellent temperature and oxidation stability and provide maximum protection of systems from heat, wear & corrosion damage. L-609-AL Anti-Leak Hydraulic Oil is fortified with the following additives for optimum performance:

Rust & Oxidation Inhibitors  
 Heat Dissipants  
 Viscosity Index Improvers

Anti-Wear Additives  
 Demulsifiers  
 Stabilizing Additives

Anti-Foam Additives  
 Seal Conditioners  
 Friction Modifiers

### **APPLICATIONS**

Forklifts/Draglines/Cranes/Shovels/Dump trucks/Balers/Hydraulic presses/Hydraulic elevators/Cherry pickers/Hydra-lifts/Hoist/Winches/Hydraulic jacks/Injection molding presses/Tractors and construction equipment.

<u><b>SPECIFICATIONS</b></u>				
ISO Grade	32	68	100	150
SAE Grade	10	20	30	40
Viscosity @ 100 °F, SUS	170	324	615	750
Viscosity @ 210 °F, SUS	43/47	53/58	65/69	75/79
Viscosity Index	95	95	95	95
Flash point, °F	400	400	415	430
Pour Point, °F	0	+5	+10	+10
Demulsibility Test D-1401	Pass	Pass	Pass	Pass
Rust Test D-665A & B	Pass	Pass	Pass	Pass
Anti-Wear Treated	Yes	Yes	Yes	Yes

**For Product Information Sheets and Material Safety Data Sheets,  
 Please visit our website: [BatonRougeIndustries.com](http://BatonRougeIndustries.com)**