


MATERIAL SAFETY DATA



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

| IDENTITY INFORMATION | |
|--|---|
| NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special- - | HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B |
| Manufactured By: Baton Rouge Industries Inc. Address: P.O. Box 26 5319 Groom Rd. Address: Baker, La. 70714 | DOT Hazard Classification: Non-Hazardous Identity : L-613-S AUTOMATIC TRANSMISSION FLUID |
| Phone: 225-775-3362 | MSDS Number: L-613-S Supersedes All Prior |
| Emergency Response Number: 800-232-0334 | Date Prepared: 10-01-09 Prepared By: David Beasley |
| NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA | |
| Information Calls: 800-232-0334 | |

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

| COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater) | CAS Number | SARA III LIST | OSHA PEL (ppm) | ACGIH TLV (ppm) | Carcinogen Ref. Source ** |
|---|------------|---------------|----------------------------|----------------------------|---------------------------|
| PETROLEUM OIL MIXTURE | 8002-05-9 | No | 5mg/M3 TWA for oil mist | 5mg/M3 TWA for oil mist | d |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

| | |
|--|--|
| Boiling Point: >450°F | Specific Gravity (H2O=1): 0.88 |
| Vapor Pressure: PSIG @ 70°F (Aerosols): N/A | Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): <0.01 |
| Vapor Density (Air = 1): 12 | Evaporation Rate (BUAC = 1): <0.01 |
| Solubility in Water: Negligible | Water Reactive: No |
| Appearance and Odor: Red color with oil odor. | |

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

| | | |
|--|---|--|
| FLAMMABILITY as per USA FLAME | Auto Ignition Temperature | Flammability Limits in Air by % in Volume: |
| PROJECTION TEST (aerosols) N/A | N/A | % LEL: N/D % UEL: N/D |
| FLASH POINT AND METHOD USED (non-aerosols): >400°F COC | EXTINGUISHER MEDIA: Dry chemical (preferred), carbon dioxide, foam, water. | |
| SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. | | |
| Unusual Fire & Explosion Hazards: Slight when exposed to heat or flame. Combustible at high temperatures. | | |

SECTION 4 - REACTIVITY HAZARD DATA

| | |
|---|---|
| STABILITY [X] STABLE [] UNSTABLE | HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR |
| Incompatibility (Mat. to avoid): Chlorine or oxygen. | Conditions to Avoid: Oxidizing atmospheres. |
| Hazardous Decomposition Products: Oxides of carbon. | |

SECTION 5 - HEALTH HAZARD DATA

| | |
|--|--|
| PRIMARY ROUTES OF ENTRY: [] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS | |
| ACUTE EFFECTS: | |
| Inhalation: May cause respiratory tract irritation. | Skin Contact: May cause irritation. |
| Eye Contact: May cause irritation. | |
| Ingestion: May cause vomiting, nausea, diarrhea. | |
| CHRONIC EFFECTS: None noted. | |
| Medical Conditions Generally Aggravated by Exposure: None noted. | |

EMERGENCY FIRST AID PROCEDURES

| |
|---|
| Eye Contact: Wash with large amounts of water. If irritation persists, call a physician. |
| Skin Contact: Remove contaminated clothing. Wash with soap and water. |
| Inhalation: Remove to fresh air. |
| Ingestion: DO NOT INDUCE VOMITING. Give 3-4 glasses of water. Seek medical attention. |

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

| | |
|--|--|
| Respiratory Protection (specify type): None required. | Eye Protection: Splash goggles or safety glasses. |
| Protective Gloves: Neoprene or plastic. | |
| Ventilation Requirements: None required in excess to normal ventilation. | |
| Other Protective Clothing & Equipment: Oil resistant apron. | |
| Hygienic Work Practices: Do not work in oil soaked clothing. Wash after handling. | |

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

| |
|--|
| Steps To Be Taken If Material Is Spilled Or Released: Stop flow, dike spill, eliminate all ignition sources, absorb on inert material and scrape up. |
| Waste Disposal Methods: Dispose of in accordance with local, state and federal regulations. |
| Precautions To Be Taken In Handling & Storage: Avoid prolonged exposure to mist and vapors. Avoid flames, sparks and hot surfaces. Keep containers closed. Shelf life one year. |
| Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Empty containers may contain explosive gas. |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only