



## L-614 COMPRESSOR/TURBINE OIL

Revised 10-1-09

### DESCRIPTION

L-614 Compressor/Turbine Oil is a superior quality lubricant made from hydrotreated virgin, 100% paraffin base oils with a naturally high film strength and viscosity index. This combination of ingredients along with advanced additives provides the best possible lubrication for today's high demand compressors & turbines.

### COMPOSITION

L-614 Compressor/Turbine Oil is enhanced with the following additives for optimum performance:

Anti-Wear Additives  
Viscosity Index Improvers  
Heat Dissipants

Anti-Foam Additives  
Rust & Oxidation Inhibitors  
Demulsifiers

Anti-Scuff Additives  
Anti-Sludging Additives  
Oiliness Agents

### APPLICATIONS

L-614 Compressor/Turbine Oil is formulated for use in single stage, double stage, multi-stage, reciprocating and screw compressors.

### SPECIFICATIONS

	32	68	100	150
ISO Grade	32	68	100	150
SAE Grade	10	20	30	40
Viscosity @ 100 °F, SUS	170	330	595	755
Viscosity @ 210 °F, SUS	43/47	53/58	65/69	74/78
Viscosity Index min.	110	110	110	110
Flash point, °F.	400	400	415	420
Sulfated Ash, Wt. %	.012	.012	.012	.012
Pour Point, °F	0	+5	+10	+10
Carbon Residue % max.	.08	.09	.10	.20

**For Product Information Sheets and Material Safety Data Sheets,  
Please visit our website: [BatonRougeIndustries.com](http://BatonRougeIndustries.com)**