



L-629 PURE MINERAL GEAR LUBE

Revised 10-1-09

DESCRIPTION

L-629 Pure Mineral Gear Lube SAE-90 is a superior quality lubricant specially formulated for transmissions and some gearboxes which require an API-GL-1, non-EP gear lube such as those calling for motor oil or mineral oil gear lubes.

COMPOSITION

L-629 Pure Mineral Gear Lube SAE-90 is made from 100% paraffin base oils with a naturally high film strength and viscosity index to perform well under extreme conditions of heat, cold, and everything in between. It provides excellent protection for synchronizers, bearings, and gears. In addition, L-629 Pure Mineral Gear Lube SAE-90 is fortified with the following additives to promote longer transmission and lubricant life:

Rust & Oxidation Inhibitors

Anti-Wear Additives

Anti-Foam Additives

APPLICATIONS

L-629 Pure Mineral Gear Lube SAE-90 is a non-EP, non-synthetic, mineral gear lubricant for use in automotive applications which require an API GL-1 gear lube. These applications include some manual transmissions and spiral-bevel rear axle assemblies and some worm-gear drive units sometimes used on commercial, farm, and construction equipment.

SPECIFICATIONS

SAE Grade	90
Viscosity @ 100 °F, SUS	958
Viscosity @ 210 °F, SUS	85/95
Viscosity Index	100
Flash point, °F	400
Pour Point, °F.	-25
Color	Amber