



L-617 HI-TACK CHAIN LUBE w/MOLY

Revised 10-1-09

DESCRIPTION

L-617 Hi-Tack Chain Lube w/Moly is a superior quality chain lubricant custom formulated to offer the best possible lubrication and prolong the life of chains, sprockets, rails, pins, and rollers used in heavy-duty applications. L-617 Hi-Tack Chain Lube w/Moly offers an adhesive/cohesive characteristic and clings to chains without slinging or dripping off for maximum positive lubrication.

COMPOSITION

L-617 Hi-Tack Chain Lube w/Moly is formulated with 100% paraffin base oils with naturally high film strength, penetrants to penetrate and lubricate inner pins and rollers and the following additives to provide optimum lubrication for heavy-duty applications.

Rust & Oxidation Inhibitors
Extreme Pressure Additives

Anti-Wear Additives
Friction Modifiers

Adhesive & Cohesive Additives
Molybdenum Disulfide

APPLICATIONS

L-617 Hi-Tack Chain Lube w/Moly is excellent for many applications such as industrial & agricultural chains, sprockets, rails, pins, rollers, cables, & wire ropes.

SPECIFICATIONS

Viscosity @ 100 °F, SUS	1980
Viscosity @ 210 °F, SUS	130/145
Viscosity Index	110
Flash point, °F	410
Pour Point, °F	0
Timken Load Rating	65 Lbs.

**For Product Information Sheets and Material Safety Data Sheets,
Please visit our website: BatonRougeIndustries.com**