



M-25 NON MELT RED E.P. GREASE

“The Original Red Grease”

Revised 10-1-09

DESCRIPTION

M-25 Non Melt Red E.P. Grease is a superior quality, multi-purpose E.P. grease formulated with PTFE to reduce friction and wear for heavy duty applications. M-25 Non Melt Red E.P. Grease is formulated with organically treated bentone thickeners and will not melt and run out at high temperatures.

COMPOSITION

M-25 Non Melt Red E.P. Grease is formulated with virgin, 100% paraffin base oils with the highest natural film strength and viscosity index on the market today. In addition, M-25 Non Melt Red E.P. Grease is fortified with the following additives, to enhance performance and provide optimum positive lubrication:

Rust & Oxidation Inhibitors	Anti-Wear Additives	Stabilizing Agents
Adhesive & Cohesive Additives	PTFE Resins	Oiliness Additives
Extreme-Pressure Additives	Friction Modifiers	

APPLICATIONS

M-25 Non Melt Red E.P. Grease is a versatile, multi-functional grease and is excellent in most applications where a high temperature or non-melt grease is applicable.

Chassis Lubrication	Anti-Friction Bearings	Roller Bearings	High Speed Bearings
Plain Bearings	Heavy Equipment	Sleeve Bearings	U-Joints
Slides & Ways	Flexible Couplings	Gear Motors	Fan Bearings
Conveyor Bearings	Slow Speed Bearings	Cables	

PERFORMANCE CHARACTERISTICS

M-25 Non Melt Red E.P. Grease is formulated for a wide range of applications to provide superior protection against:

Friction & Wear	Rust & Oxidation	Extreme Pressure	Shock Loads
Water Washout	Pound Out	High Temperatures	Abrasives

<u>SPECIFICATIONS</u>		
Thickener	Bentone	Bentone
Base Oil @ 100 °F, SUS	450	100
Base Oil @ 210 °F, SUS	60	60
Worked Penetration	265-295	355-385
NLGI Grade	2	0
Texture	Buttery/Stringy	Buttery
ASTM Dropping Point, °F	None	None
Timken Load Rating	65 lbs.	65 lbs.

**For Product Information Sheets and Material Safety Data Sheets,
Please visit our website: BatonRougeIndustries.com**