



L-605R AERO FLOW RACING BLEND HD MOTOR OIL

Revised 10-1-09

DESCRIPTION

L-605R Aero Flow Racing Blend HD Motor Oil is a custom formulated crankcase oil blended from hydrotreated 100% paraffin base oils and designed to meet the demands of today's high demand racing engines as well as diesel engines, naturally aspirated, turbocharged and heavy duty industrial engines.

COMPOSITION

L-605R Aero Flow Racing Blend HD Motor Oil is formulated with PTFE and Protecto-Lube to reduce friction, wear, prevent thermal breakdown and is fortified with the following additives for optimum positive lubrication and superior performance:

Rust & Oxidation Inhibitors
Dispersant Additives
Viscosity Index Improvers
Extended Drain Additives
Soot Control Additives

Anti-Wear Additives
Pour Point Depressants
Zinc Dithiophosphate
Heat Dissipants
Seal Conditioners

Anti-Foam Additives
Stabilizing Agents
Anti-Sludging Additives
Detergent Additives
Friction Modifiers

APPLICATIONS

L-605R Aero Flow Racing Blend HD Motor Oil is available in SAE 15W40, 50 & 20W50 and meets and/or exceeds most new & old car, truck and equipment warranty requirements.

<u>SPECIFICATIONS</u>			
Product Number	L-605R	L-605R	L-605R
SAE Grade	50	15W40	20W50
Viscosity @ 40°C, cSt	200	121	154
Viscosity @ 100°C, cSt	18.7	15.6	17.5
Viscosity @ 100 °F, SUS	1050	570	805
Viscosity @ 210 °F, SUS	94	78	88
Viscosity Index	101	135	120
Flash point, °F	460	438	450
Pour Point, °F	+10	-33	-22
Gravity, API	26.5	29.3	27.7
Pounds per Gallon	7.52	7.34	7.402
Sulfated Ash, % Weight	0.95	0.95	0.95
Base Number, D2896	12	12	12
Color	Red	Red	Red
API Service	CF-2/SJ	CI-4+/SL	SL

**For Product Information Sheets and Material Safety Data Sheets,
Please visit our website: BatonRougeIndustries.com**