

# SAFETY DATA SHEET



**Baton Rouge Industries, Inc.**  
5319 Groom Road • P.O. Box 26  
Baker, Louisiana 70714  
1-800-232-0334 • 225-775-3362  
FX 225-775-3498  
**BatonRougeIndustries.com**

## 1. Identification

**Product identifier** **C-143 Dri-Mol (Aerosol)**  
**Company information** **BATON ROUGE INDUSTRY, INC.**  
**5319 GROOM ROAD**  
**BAKER, LA 70714 United States**  
**General Assistance 800-232-0334**

**Company phone**  
**Emergency telephone US** 1-866-836-8855  
**Emergency telephone outside US** 1-952-852-4646

**Version #** 01  
**Recommended use** Lubricant  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1

**Health hazards** Acute toxicity, oral Category 4  
Germ cell mutagenicity Category 1  
Carcinogenicity Category 1  
Reproductive toxicity Category 1A  
Specific target organ toxicity, single exposure Category 1  
Specific target organ toxicity, repeated exposure Category 2

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3  
Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Harmful if swallowed. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs. May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement**  
**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If swallowed: Call a poison center/doctor if you feel unwell. If exposed: Call a poison center/doctor. Specific treatment (see this label). Rinse mouth.

**Storage** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methylene Chloride		75-09-2	40 - 60
Butane		106-97-8	10 - 20
Propane		74-98-6	2.5 - 10
Toluene		108-88-3	2.5 - 10
Propylene Oxide		75-56-9	0.1 - 1

Other components below reportable levels 2.5 - 10

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.
<b>Most important symptoms/effects, acute and delayed</b>	Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Powder. Water. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. Extremely flammable aerosol.
<b>General fire hazards</b>	

### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Do not breathe gas. Do not taste or swallow. Avoid contact during pregnancy/while nursing. Use only in well-ventilated areas. Use personal protective equipment as required. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains.

### Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

##### Components

##### Value

Methylene Chloride (CAS 75-09-2)	STEL	125 ppm
	TWA	25 ppm

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

##### Components

##### Value

Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm
Propylene Oxide (CAS 75-56-9)	PEL	240 mg/m3 100 ppm

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

##### Components

##### Type

##### Value

Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

#### US. ACGIH Threshold Limit Values

##### Components

##### Type

##### Value

Butane (CAS 106-97-8)	STEL	1000 ppm
Methylene Chloride (CAS 75-09-2)	TWA	50 ppm
Propylene Oxide (CAS 75-56-9)	TWA	2 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

##### Components

##### Value

Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

##### Components

Value

##### Determinant

##### Specimen

##### Sampling Time

Methylene Chloride (CAS 75-09-2)	0.3 mg/l	Dichloromethane	Urine	*
----------------------------------	----------	-----------------	-------	---

**ACGIH Biological Exposure Indices  
Components Value**

		<b>Determinant</b>	<b>Specimen</b>	<b>Sampling Time</b>
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

Toluene (CAS 108-88-3) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

Toluene (CAS 108-88-3) Skin designation applies.

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates **Appropriate engineering controls** should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

Wear safety glasses with side shields (or goggles). **Eye/face**

**protection****Hand protection**

Wear protective gloves.

**Skin protection****Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Not available.

**Odor**

Not available.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

75.39 °F (24.11 °C) estimated

**Flash point**

-156.0 °F (-104.4 °C) Propellant estimated

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not available.

**Upper/lower flammability or explosive limits**

Not available. **Flammability**

**limit - lower**

(%)

**Flammability limit - upper**

Not available.

(%)

**Explosive limit - lower (%)**

Not available.

**Explosive limit - upper (%)**

Not available.

**Vapor pressure**

461.58 psig @70F estimated

**Vapor density**

Not available.

**Relative density**

0.334 g/cm<sup>3</sup> estimated

<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	0.33 g/cm3 estimated
<b>Flammability class</b>	Flammable IA estimated
<b>Heat of combustion</b>	16.08 kJ/g estimated
<b>Heat of combustion (NFPA 30B)</b>	16.08 kJ/g estimated
<b>Percent volatile</b>	95.68 % estimated
<b>Specific gravity</b>	0.334 estimated
<b>VOC (Weight %)</b>	95.77 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point.
<b>Incompatible materials</b>	Strong oxidizing agents. Fluorine. Chlorine. Nitrates.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Harmful if swallowed. **Ingestion**

<b>Inhalation</b>	May cause damage to organs by inhalation.
<b>Skin contact</b>	Not available.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

**Acute toxicity** Harmful if swallowed.

Components	Species	Test Results
Butane (CAS 106-97-8)		
<b>Acute</b> <i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Methylene Chloride (CAS 75-09-2)		
<b>Acute</b> <i>Dermal</i> LD50	Rat	> 2000 mg/kg, Days
	<i>Inhalation</i> LC50	Mouse 49 mg/l, 7 Hours

Components	Species	Test Results
Propane (CAS 74-98-6)		
<b>Acute</b> <i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52 %, 120 Minutes 1355 mg/l 658 mg/l/4h
Propylene Oxide (CAS 75-56-9)		
<b>Acute</b> <i>Dermal</i> LD50	Rabbit	950 - 1250 mg/kg, 4 Hours 1.5 ml/kg, 4 Hours
<i>Inhalation</i> LC50	-	4197 ppm, 4 Hours 4124 mg/m3, 4 Hours
<i>Oral</i> LD50	Rat	382 - 587 mg/kg
Toluene (CAS 108-88-3)		
<b>Acute</b> <i>Dermal</i> LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i> LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 12.5 - 28.8 mg/l, 4 Hours
<i>Oral</i> LD50	Rat	5000 mg/kg

\* Estimates for product may be based on additional component data not shown.

Prolonged skin contact may cause temporary irritation. **Skin**

**corrosion/irritation**

**Serious eye damage/eye irritation**

Direct contact with eyes may cause temporary irritation.

**Respiratory or skin sensitization**

Not available. **Respiratory**

**sensitization**

**Skin sensitization**

This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**

May cause genetic defects.

**Carcinogenicity**

May cause cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Methylene Chloride (CAS 75-09-2) 2B Possibly carcinogenic to humans.

Propylene Oxide (CAS 75-56-9) 2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Methylene Chloride (CAS 75-09-2) Cancer

**US. National Toxicology Program (NTP) Report on Carcinogens**

Methylene Chloride (CAS 75-09-2) Reasonably Anticipated to be a Human Carcinogen.

Propylene Oxide (CAS 75-56-9) Reasonably Anticipated to be a Human Carcinogen.

May damage fertility or the unborn child. **Reproductive toxicity**

**Specific target organ toxicity - single exposure**

Causes damage to organs.

<b>Specific target organ toxicity - repeated exposure</b>	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not likely, due to the form of the product.
<b>Chronic effects</b>	Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Components		Species	Test Results
Methylene Chloride (CAS 75-09-2)			
<b>Aquatic</b>			
Algae	IC50	Algae	500.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1689.5 mg/L, 48 Hours
		Water flea (Daphnia magna)	1250 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	140.8 - 277.8 mg/l, 96 hours
Propylene Oxide (CAS 75-56-9)			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	350 mg/L, 48 Hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. **Persistence and**

### degradability

**Bioaccumulative potential** No data available.

### Partition coefficient n-octanol / water (log Kow)

Butane	2.89
Methylene Chloride	1.25
Propane	2.36
Propylene Oxide	0.03
Toluene	2.73

No data available. **Mobility in soil**

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations.

### Local disposal regulations

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

### US RCRA Hazardous Waste U List: Reference

Methylene Chloride (CAS 75-09-2)U080  
Toluene (CAS 108-88-3)U220

Dispose of in accordance with local regulations. Empty containers or liners may retain some **Waste from residues /**

### unused

product residues. This material and its container must be disposed of in a safe manner (see: **products** Disposal instructions).

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

**14. Transport information**

<b>DOT</b>	
<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	
<b>Subsidiary risk</b>	2.1
<b>Label(s)</b>	6.1(PGIII)
<b>Packing group</b>	2.1, 6.1
<b>Special precautions for user</b>	Not applicable. Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
	<b>N82Special provisions</b>
	<b>306Packaging exceptions</b>
	None <b>Packaging non bulk</b>
	None <b>Packaging bulk</b>
	This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.
<b>IATA</b>	
	UN1950 <b>UN number</b>
<b>Transport hazard class(es)</b>	Aerosols, flammable, containing substances in Division 6.1, Packing Group III <b>UN proper shipping name</b>
	2.1 <b>Class</b>
	6.1(PGIII) <b>Subsidiary risk</b>
	2.1, 6.1 <b>Label(s)</b>
	Not applicable. <b>Packing group</b>
	No. <b>Environmental hazards</b>
	10 <b>PERG Code</b>
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>aircraft</b>	Allowed. <b>Passenger and cargo</b>
	Allowed. <b>Cargo aircraft only</b>
	LTD QTY <b>Packaging Exceptions</b>
<b>IMDG</b>	
	UN1950 <b>UN number</b>
<b>Transport hazard class(es)</b>	AEROSOLS <b>UN proper shipping name</b>
	2.1 <b>Class</b>
	6.1(PGIII) <b>Subsidiary risk</b>
	2.1+6.1 <b>Label(s)</b>
	Not applicable. <b>Packing group</b>
<b>Environmental hazards</b>	
	No. <b>Marine pollutant</b>
	F-D, S-UE <b>mS</b>
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. NOT a LTD QTY <b>Packaging Exceptions</b>
	Not applicable. <b>Transport in bulk according to</b>
<b>Annex II of MARPOL 73/78 and the IBC Code</b>	



DOT



IATA; IMDG



### 15. Regulatory information

#### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Methylene Chloride (CAS 75-09-2) Listed.

Propylene Oxide (CAS 75-56-9) Listed.

Toluene (CAS 108-88-3) Listed.

#### SARA 304 Emergency release notification

Propylene Oxide (CAS 75-56-9) 100 LBS

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Methylene Chloride (CAS 75-09-2) Cancer

Heart  
 Central nervous system  
 Liver  
 Skin irritation  
 Eye irritation

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity
---------------	------------	---------------------

Propylene Oxide	75-56-9	100
-----------------	---------	-----

Threshold planning quantity
-----------------------------

10000 lbs
-----------

Threshold planning quantity, lower value
--

Threshold planning quantity, upper value
--

SARA 311/312 Hazardous chemical	No
---------------------------------	----

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methylene Chloride	75-09-2	40 - 60
Toluene	108-88-3	2.5 - 10
Ethylene Glycol	107-21-1	0.1 - 1
Methanol	67-56-1	0.1 - 1
Propylene Oxide	75-56-9	0.1 - 1

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methylene Chloride (CAS 75-09-2)  
Propylene Oxide (CAS 75-56-9)  
Toluene (CAS 108-88-3)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)  
Propylene Oxide (CAS 75-56-9)

Not regulated. **Safe Drinking Water Act**

(SDWA)

### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3)6594

### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3)35 %WV

### DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3)594

## US state regulations

### US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)  
Methylene Chloride (CAS 75-09-2)  
Propane (CAS 74-98-6)  
Propylene Oxide (CAS 75-56-9)  
Toluene (CAS 108-88-3)

### US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)  
Methylene Chloride (CAS 75-09-2)  
Propane (CAS 74-98-6)  
Propylene Oxide (CAS 75-56-9)  
Toluene (CAS 108-88-3)

### US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)  
Methylene Chloride (CAS 75-09-2)  
Propane (CAS 74-98-6)  
Propylene Oxide (CAS 75-56-9)  
Toluene (CAS 108-88-3)

### US. Rhode Island RTK

Butane (CAS 106-97-8)  
Methylene Chloride (CAS 75-09-2)  
Propane (CAS 74-98-6)  
Propylene Oxide (CAS 75-56-9)  
Toluene (CAS 108-88-3)

### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methylene Chloride (CAS 75-09-2)Listed: April 1, 1988  
Propylene Oxide (CAS 75-56-9)Listed: October 1, 1988

#### US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1)Listed: March 16, 2012  
Toluene (CAS 108-88-3)Listed: January 1, 1991

#### US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)Listed: August 7, 2009

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 12-22-2014

**Version #** 01

**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.  
Product and Company Identification: Product and Company Identification

**Revision Information**