

PRODUCT INFORMATION



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

C-144 WHITE LITHIUM SPRAY GREASE (AEROSOL)

01/01/18

DESCRIPTION

C-144 White Lithium Spray Grease (Aerosol) is white lithium grease in a convenient, easy-to-use aerosol can. It is an exceptional coating for the prevention of rust & corrosion. In addition, this PTFE fortified, durable, nonstaining lubricant provides superior friction reduction between similar or different materials than other competing brands, will not run, wash off, or freeze and does not gum or cake. Use this product on battery terminals, brake cables, distributor caps, latches, hinges, bolts, locks, antennas, equipment, tools, tracks, glides, bearings, rollers, buckles, shackles, winch gears, and other external moving parts or exposed surfaces. Applications for this product can be found in the packaging industry, automotive field, marine and aircraft maintenance. This next generation product is formulated without chlorinated solvents or ozone depleters.

DANGER

Contains Hexane and Petroleum Distillates. Extremely flammable. Use only in a well ventilated area. Do not use near heat, sparks, open flame or other sources of ignition. Do not smoke in use area. Harmful or fatal if swallowed. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures about 120 °F. KEEP OUT OF REACH OF CHILDREN.

SPILL OR LEAKAGE PROCEDURES

Cover with absorbent material and sweep up. Wash area to prevent slipping. Incinerate or landfill according to local, state or federal regulations. Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

<u>SPECIFICATIONS</u>	
Net Wt.	11 ounces
USDA Category	H-1
Classification	Aerosol Grease Lubricant
General Appearance	Thin Liquid Which Gels
Color	White
Odor	Solvent Odor
Vapor Pressure @ 70° F	46 psig
Spray Pattern	Forceful Light Mist
Flammability	Extremely Flammable
NFPA Code 30B	Level 3