

## PRODUCT INFORMATION



Baton Rouge Industries, Inc.  
5319 Groom Road • P.O. Box 26  
Baker, Louisiana 70714  
1-800-232-0334 • 225-775-3362  
FX 225-775-3498  
BatonRougeIndustries.com

# L-605-FS 10w30 Aero Flow HD Motor Oil (Full Synthetic)

01/01/18

### DESCRIPTION

**L-605-FS Full Synthetic 10W30 Motor Oil** provides high quality engine protection under all driving conditions and is formulated with full synthetic base stocks and a premium additive package to provide extra protection against the harmful effects of city driving, where cars undergo a higher stress due to constant stopping and going.

**L-605-FS Full Synthetic 10W30 Motor Oil** low friction formula helps improve gas mileage for long engine life and helps protect against rust, corrosion, startup wear, varnish build-up, and eliminates the need for extra oil additives. It also protects against thermal breakdown which helps prevent stuck rings.

### FEATURES/BENEFITS

- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down

### APPLICATION

**L-605-FS Full Synthetic 10W30 Motor Oil** meets requirements of API SN service. **L-605-FS Full Synthetic 10W30 Motor Oil** meets or exceeds the demanding requirements of International Lubricant Standardization and Approval Committee (ILSAC) GF-5, GF-4, GF-3, GF-2. ILSAC GF-5 comprises the latest standard for passenger car, van, light truck and sport utility vehicles motor oils. This product is also recommended for older engines, which owner's manual calls for API SN, SM, SL, SJ, SH, SG, SF, SE Service Classifications or any combination thereof. Viscosity recommendations vary according to temperature and engine manufacturer.

### PERFORMANCE CAPABILITIES

- Chrysler MS6395

### SPECIFICATIONS

SAE GRADE	10W30
Specific Gravity, (60°F)	0.8566
Viscosity, @ 40°C, cSt	61.1
Viscosity, @ 100°C, cSt	10.0
Viscosity Index	149
Cold Crank, cP at °C, Max	7000 @ -25C
Flash Point, °F	434
Pour Point, °C (°F)	-29 (-20)
Noack Volatility %, Max	13
High Temp/High Shear Visc, cP @150°C, Min	2.9
Color	2.5
Phosphorus, wt%	0.07
Zinc, wt%	0.08