

## PRODUCT INFORMATION



Baton Rouge Industries, Inc.  
5319 Groom Road • P.O. Box 26  
Baker, Louisiana 70714  
1-800-232-0334 • 225-775-3362  
FX 225-775-3498  
BatonRougeIndustries.com

# L-615-XL

## Multi VIS Power-Fluid – Extra Life J20C

(Multi VIS Universal Hydraulic / Transmission Fluid)  
(SAE 10W30)

01/01/18

### DESCRIPTION

*Multi VIS L-615-XL Power –Fluid – Extra Life J20C* is formulated specially for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment which employs a common fluid reservoir.

*Multi VIS L-615-XL Power –Fluid – Extra Life J20C* is manufactured with the highest quality base stocks, a viscosity index improver, oxidation and corrosion inhibitors, antiwear and film strength additives, an antifoaming agent, and a pour point depressant.

### FEATURES/BENEFITS

- Meets the needs of modern tractors for a combination lubricant
- Performs many functions such as lubrication of the transmission and final drive
- Serving as hydraulic fluid for the operation of power steering units, brakes and implements
- Eliminates “chatter” and excessive brake facing wear, assuring smooth operation of clutch packs and wet brakes.
- Protects metal surfaces against scuffing and wear.
- Compatible with equipment manufacturer’s proprietary fluids and other fluids of this type.

### APPLICATION

*Multi VIS L-615-XL Power –Fluid – Extra Life J20C* is formulated specifically to meet John Deere J20C specifications. It is recommended for use as a multi-functional fluid in all type of farm equipment and tractors.

#### **Meets Performance Requirements:**

- AGCO – improved power fluid 821XL, Power Fluid 821
- API GL-4 (not recommended for hypoid gear oil applications)
- John Deere – J20C, Quatrol<sup>®</sup>, Hy-gard<sup>®</sup>
- **L-615-XL Meets and exceeds John Deere 303 Specs**
- Ford New Holland – ESN-M2C134-D, FNHA-2-C-201
- Massey Ferguson – M1135, M1141, M1143, M1145
- HTF 272843, 257541, 246634
- White Farm Equipment – Q-1826
- Case Corporation – JIC-143, JIC-145, MS 1206, MS 1207, MS 1209, MS 1210
- Oliver – Type 55
- Caterpillar – TO-2
- Renk Doromat - 873, 874 A/B

- Allison C-4
- Kubota UDT
- Komatsu Dresser
- Versatile Specification 23M or 24M
- International Harvester B6
- Volvo – VME, WB 101
- Fiat-Hesson Multi-G
- ZF TE-ML-03E
- And many others...

® - Quatrol and Hy-gard are registered trademarks of John Deere and not a specification. XL Tractor Hydraulic Fluid may be used where Quatrol or Hy-gard is called for.

**\* ALWAYS CONSULT YOUR OWNER’S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.**

### TYPICAL TEST DATA

Product Specifications	Results
Specific Gravity @ 60 °F	0.8690
Viscosity, Kinematic cSt at 40°C	55
cSt at 100°C	9.4
Viscosity Index	154
Viscosity, Brookfield cP at -34.4°C Max	70,000
Flash Point, °F	403
Pour Point, °C (°F)	-35 (-31)
Color	1.5

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

For Product Information Sheets and Safety Data Sheets,  
please visit our website: [BatonRougeIndustries.com](http://BatonRougeIndustries.com)