

PRODUCT INFORMATION



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

L-622 WIRE ROPE & FIFTH WHEEL GREASE

01/01/18

DESCRIPTION

L-622 Wire Rope & Fifth Wheel Grease is a superior quality organo-clay base lubricant, formulated for heavy industrial applications. It has a pronounced tackiness and extreme-pressure characteristics to reduce wear, friction and provide optimum lubrication for wire ropes, cables and fifth wheels.

COMPOSITION

L-622 Wire Rope & Fifth Wheel Grease is formulated with 100% paraffin base oils, organo-clay thickeners, and will not melt or run off when exposed to high temperatures. In addition, L-622 Wire Rope & Fifth Wheel Grease is enhanced with the following additives to provide optimum lubrication for heavy duty applications:

Rust & Oxidation Inhibitors	Anti-Wear Additives	Molybdenum Disulfide
Friction Modifiers	Oiliness Additives	Stabilizing Agents
Adhesive & Cohesive Additives	Extreme-Pressure Additives	Contains Teflon

APPLICATIONS

L-622 Wire Rope & Fifth Wheel Grease is excellent for lubricating cables, wire ropes, slings & truck fifth wheels and can be applied by paddle or brush.

SPECIFICATIONS

Thickener Type	Bentone
Thickener Vol. %	5-6
Base Oil @ 100°F, SUS	450
Base Oil @ 210°F, SUS	60
Worked Penetration	265-295
NLGI Grade	2
Texture	Smooth/Tacky
Dropping Point	Non-Melt
Timken Load Rating	65 lbs.