

PRODUCT INFORMATION



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

L-605-FS 10w40 Aero Flow HD Motor Oil (Full Synthetic)

01/01/18

DESCRIPTION

L-605-FS 10W40 Motor Oil provides high quality engine protection under all driving conditions and is formulated with full synthetic base stocks and a premium additive package to provide extra protection against the harmful effects of city driving, where cars undergo a higher stress due to constant stopping and going.

L-605-FS 10W40 Motor Oil low friction formula helps improve gas mileage for long engine life and helps protect against rust, corrosion, startup wear, varnish build-up, and eliminates the need for extra oil additives. It also protects against thermal breakdown which helps prevent stuck rings.

FEATURES/BENEFITS

- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down

APPLICATION

L-605-FS 10W40 Motor Oil meets requirements of API SN service. This product is also recommended for older engines, which owner's manual calls for API SN, SM, SL, SJ, SH, SG, SF, SE Service Classifications or any combination thereof. Viscosity recommendations vary according to temperature and engine manufacturer.

SPECIFICATIONS

SAE GRADE	10W40
Specific Gravity, (60°F)	0.8556
Viscosity, @ 40°C, cSt	84.6
Viscosity, @ 100°C, cSt	13.2
Viscosity Index	157
Cold Crank, cP at °C, Max	7000 @ -25C
Flash Point, °F	443
Pour Point, °C (°F)	-27 (17)
Noack Volatility %, Max	15
High Temp/High Shear Visc, cP @150°C, Min	3.5
Color	2.5
Phosphorus, wt%	0.07
Zinc, wt%	0.08