

## PRODUCT INFORMATION



Baton Rouge Industries, Inc.  
5319 Groom Road • P.O. Box 26  
Baker, Louisiana 70714  
1-800-232-0334 • 225-775-3362  
FX 225-775-3498  
[BatonRougeIndustries.com](http://BatonRougeIndustries.com)

# L-625 140W Power Gear E.P. Gear Lubricant Red Dye added for leak traceability

03/01/2020

### DESCRIPTION

*L-625 Power Gear E.P. Gear Lubricant* is a climbing gear oil manufactured with high quality base stocks to provide outstanding oxidation stability for long service life. This oil is inhibited against foaming and does not contribute to corrosion or wear of yellow metals, such as brass or bronze.

### FEATURES/BENEFITS

- Climbing gear lube due to added tackifier
- Anti-Wear
- Non-foaming
- 300,000-mile drain interval
- Non-corrosive
- Extreme pressure
- Does Not Mix with Water
- Limited Slip
- Rust inhibitors

### APPLICATION

*L-625 Power Gear E.P. Gear Lubricant* is designed for use in manual transmissions and transfer cases in on-highway trucks and off-highway equipment, which require an API GL-1 gear lubricant. It may also find use in some industrial gear oil applications where viscosity grade is recommended.

**\* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.**

### TYPICAL TEST DATA

SAE GRADE	140
Specific Gravity @ 60 °F	0.9220
Viscosity, Kinematic cSt at 40°C cSt at 100°C	405 30
Viscosity Index	105
Flash Point, °F	429
Pour Point, °C (°F)	-23 (-9)
Color	Red

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

For Product Information Sheets and Safety Data Sheets,  
please visit our website: [BatonRougeIndustries.com](http://BatonRougeIndustries.com)