

PRODUCT INFORMATION



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

C-143 DRI-MOL LUBRICANT (AEROSOL)

01/01/18

DESCRIPTION

C-143 Dri Mol Lubricant (Aerosol) is a molybdenum disulfide formulation which dries to a hard, black coating very quickly. It adheres to many substrates, especially metal, with minimal surface preparation. It resists wear and abrasion, provides high lubricity, gives excellent extreme-pressure properties and is stable at extreme temperatures, both high and low. Typical applications for this moly lubricant are chain lubricating, maintenance on furnaces, kilns, ovens, conveyors, gasket coating, anti-seize, and mold release, etc. This advanced formula contains no chlorinated solvents or ozone depleters and is ideal for use throughout general industry.

DANGER

Contains hexane, acetone, isobutane/propane blend, and isopropyl alcohol. Extremely flammable. Use only in a well ventilated area. Do not use near heat, sparks, open flame or other sources of ignition. Do not smoke in use area. Harmful or fatal if swallowed. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120 °F. KEEP OUT OF REACH OF CHILDREN.

SPILL OR LEAKAGE PROCEDURES

Do not flush to sewer. Absorb with suitable material and dispose of according to local, state and federal regulations. Aerosol cans when ventilated to atmospheric pressure through normal use, pose no disposal hazard.

<u>SPECIFICATIONS</u>	
Net Wt.	14 ounces
Classification	Aerosol Dri Mol Lubricant
General Appearance	Opaque, Film-Forming Lubricant
Color	Gray/Black
Odor	Solvent
Vapor Pressure @ 70° F	60 psig
Spray Pattern	Mist
Flammability	Extremely Flammable
NFPA Code 30B	Level 3