

## PRODUCT INFORMATION



Baton Rouge Industries, Inc.  
5319 Groom Road • P.O. Box 26  
Baker, Louisiana 70714  
1-800-232-0334 • 225-775-3362  
FX 225-775-3498  
BatonRougeIndustries.com

# L-605-FS 5w40 Aero Flow HD Motor Oil (Full Synthetic)

01/01/18

### DESCRIPTION

*L-605 Full Synthetic 5W40 Motor Oil* provides high quality engine protection under all driving conditions and is formulated with full synthetic base stocks and a premium additive package to provide extra protection against the harmful effects of city driving, where cars undergo a higher stress due to constant stopping and going.

*L-605 Full Synthetic 5W40 Motor Oil* low friction formula helps improve gas mileage for long engine life and helps protect against rust, corrosion, startup wear, varnish build-up, and eliminates the need for extra oil additives. It also protects against thermal breakdown which helps prevent stuck rings.

### FEATURES/BENEFITS

- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down

### APPLICATION

*L-605 Full Synthetic 5W40 Motor Oil* meets requirements of API SN service. This product is also recommended for older engines, which owner's manual calls for API SN, SM, SL, SJ, SH, SG, SF, SE Service Classifications or any combination thereof. Viscosity recommendations vary according to temperature and engine manufacturer.

### SPECIFICATIONS

SAE GRADE	5W40
Specific Gravity, (60°F)	0.8508
Viscosity, @ 40°C, cSt	81.8
Viscosity, @ 100°C, cSt	13.6
Viscosity Index	170
Cold Crank, cP at °C, Max	6600 @ -30C
Flash Point, °F	411
Pour Point, °C (°F)	-30 (-22)
Noack Volatility %, Max	15
High Temp/High Shear Visc, cP @150°C, Min	3.5
Color	2.5
Phosphorus, wt%	0.07
Zinc, wt%	0.08