

PRODUCT INFORMATION



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

L-628 Power Gear E.P. Gear Lubricant Red Dye added for leak traceability w/moly (Straight 90)

01/01/18

DESCRIPTION

L-628 Power Gear E.P. Gear Lubricant w/moly is manufactured with high quality base stocks to provide outstanding oxidation stability for long service life. This oil is inhibited against foaming and does not contribute to corrosion or wear of yellow metals, such as brass or bronze.

FEATURES/BENEFITS

- Long service life
- Non-foaming
- Non-corrosive
- Anti-wear
- Extreme pressure
- Limited slip
- Tackifiers
- Rust inhibitors

APPLICATION

L-628 Power Gear E.P. Gear Lubricant is designed for use in manual transmissions and transfer cases in on-highway trucks and off-highway equipment, which require an API GL-1 gear lubricant. It may also find use in industrial gear oil applications that call for a straight mineral oil in the SAE 50 engine oil viscosity weight range. (The SAE 50 engine oil viscosity grade is approximately equal to the SAE 90 gear oil viscosity grade).

*** ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.**

TYPICAL TEST DATA

SAE GRADE	90
Specific Gravity @ 60 °F	0.9220
Viscosity, Kinematic cSt at 40°C	241
cSt at 100°C	14.8
Viscosity Index	90 min
Flash Point, °F	429
Pour Point, °C (°F)	-23 (-9)
Color	red

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

For Product Information Sheets and Safety Data Sheets,
please visit our website: BatonRougeIndustries.com