

PRODUCT INFORMATION



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

L-605-SB 40W Aero Flow HD Motor Oil (Synthetic Blend)

01/01/18

DESCRIPTION

L-605-SB SAE 40 Motor Oil provides high quality engine protection under all driving conditions and is specifically formulated to provide extra protection against the harmful effects of city driving.

L-605-SB SAE 40 Motor Oil low friction formula helps improve gas mileage, extend engine life and helps protect against rust, corrosion, startup wear and varnish build-up. It also protects against thermal breakdown which helps prevent stuck rings.

FEATURES/BENEFITS

- 10 TBN for longer drain intervals
- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down

APPLICATION

- On the highway applications for light and heavy duty trucking.
- Off the highway applications such as trucking, construction, agriculture and quarrying.
- Various mixed fleet applications.

PERFORMANCE CAPABILITIES

- API CF-4, CD
- API SL, SJ, SH, SG

SPECIFICATIONS

| SAE GRADE | 40 |
|-------------------------------------|-----------|
| Specific Gravity @ 60 °F | 0.8911 |
| Viscosity, Kinematic cSt at 40°C | 133 |
| cSt at 100°C | 15.5 |
| Viscosity Index | 121 |
| Flash Point, °F | 432 |
| Pour Point, °C (°F) | -24 (-11) |
| Color, Max | 4.5 |
| TBN | 10+ |