

PRODUCT INFORMATION



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

C-139 DE AQUA LUBE (AEROSOL)

01/01/18

DESCRIPTION

C-139 De Aqua Lube (Aerosol) is a combination of penetrating lubricants (contain P.T.F.E.), moisture displacements compounds, solvents and corrosion inhibitors. It is used as a penetrating oil to loosen parts, which have become frozen by corrosion, and to displace moisture from electrical equipment such as contact points and automotive distributors, machinery parts, guns and equipment. C-139 De Aqua Lube (Aerosol) is used by factories, truck lines, delivery services, transit systems, machine shops, service stations, auto repair shops, farms, and general industries. **IMPORTANT:** Conforms to Military Specification MIL-C-23411 for corrosion prevention.

HEALTH HAZARD DATA

Vapor harmful. Contains Perchloroethylene and Trichloroethylene. Use with adequate ventilation to keep exposure levels below the 25 parts per million O.S.H.A permissible exposure limit (PEL) during an eight hour period (time weighted average). Consult the product material safety data sheet for additional information regarding exposure concerns. Avoid inhalation of spray mist or vapors. If overcome by fumes, remove victim to fresh air. Resuscitate if necessary. Get medical attention. Avoid contact with eyes and skin. In case of eye contact, flush immediately with plenty of water and continue for 15 minutes. If discomfort persists, see a physician. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120° F. **WARNING: KEEP OUT OF REACH OF CHILDREN.**

SPILL OR LEAKAGE PROCEDURES

Do not flush to sewer. Absorb with suitable material and dispose of according to local, state and deferral regulations. Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

SPECIFICATIONS

Net Wt.	14 ounces
USDA Category	H-2
Classification	Aerosol 4-in-1 Corrosion Preventer
General Appearance	Clear Liquid
Color	Light Brown
Odor	Solvent
Vapor Pressure @ 70° F	85-100 psig
Spray Pattern	Mist
Flammability	Flammable
NFPA Code 30B	Level 1