


MATERIAL SAFETY DATA



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

IDENTITY AND DISTRIBUTOR'S INFORMATION					
NFPA Rating: Health-1; Flammability-2; Reactivity-0; Special- -			HMIS Rating: Health-1; Flammability-2; Reactivity-0; Personal Protection-H		
Manufactured By: Baton Rouge Industries Inc. Address: P.O. Box 26 5319 Groom Rd. Address: Baker, La. 70714			DOT Hazard Classification: Combustible 2 Identity L-673-10 CABLE COATING (BLACK)		
Phone: 225-775-3362			MSDS Number: L-673-10 Supersedes All Prior		
Emergency Response Number: 800-232-0334			Date Prepared: 08/27/12 Prepared By: David Beasley		
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA			Information Calls: 800-232-0334		
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
HAZARDOUS COMPONENTS/CHEMICAL NAMES AND COMMON NAMES	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	% by wt.
PETROLEUM OIL MIXTURE	8002-05-9	No	5mg/M3 TWA for oil mist	5mg/M3 TWA for oil mist	
Mineral Spirits	8052-41-3	No	500ppm	500 ppm	<20
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: 320° F			Specific Gravity (H2O=1): 0.88		
Vapor Pressure: <5mmHg			Vapor Pressure <5mmHg		
Vapor Density (Air = 1): >3			Evaporation Rate N/A		
Solubility in Water: Nil			Water Reactive: No		
Appearance and Odor: Black with oil odor.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY N/A		Auto Ignition Temperature >400° F		Flammability Limits in Air by % in Volume: % LEL: 0.9 % UEL: 7.0	
FLASH POINT AND METHOD USED (non-aerosols): 105° F COC			EXTINGUISHER MEDIA: Dry chemical (preferred), carbon dioxide, foam, water.		
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.					
Unusual Fire & Explosion Hazards: Slight when exposed to heat or flame. Combustible at high temperatures.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [X] STABLE [] UNSTABLE			HAZARDOUS POLYMERIZATION [] WILL [X] MAY OCCUR		
Incompatibility (Mat. to avoid): Chlorine or oxygen.			Conditions to Avoid: Oxidizing atmospheres.		
Hazardous Decomposition Products: Oxides of carbon.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS					
ACUTE EFFECTS:					
Inhalation: May cause respiratory tract irritation.					
Eye Contact: May cause irritation.			Skin Contact: May cause irritation.		
Ingestion: May cause vomiting, nausea, diarrhea.					
CHRONIC EFFECTS: None noted.					
Medical Conditions Generally Aggravated by Exposure: None noted.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Wash with large amounts of water. If irritation persists, call a physician.					
Skin Contact: Remove contaminated clothing. Wash with soap and water.					
Inhalation: Remove to fresh air.					
Ingestion: DO NOT INDUCE VOMITING. Give 3-4 glasses of water. Seek medical attention.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
Respiratory Protection (specify type): None required.					
Protective Gloves: Neoprene or plastic.			Eye Protection: Splash goggles or safety glasses.		
Ventilation Requirements: None required in excess to normal ventilation.					
Other Protective Clothing & Equipment: Oil resistant apron.					
Hygienic Work Practices: Do not work in oil soaked clothing. Wash after handling.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Stop flow, dike spill, eliminate all ignition sources, absorb on inert material and scrape up.					
Waste Disposal Methods: Dispose of in accordance with local, state and federal regulations.					
Precautions To Be Taken In Handling & Storage: Avoid prolonged exposure to mist and vapors. Avoid flames, sparks and hot surfaces. Keep containers closed. Shelf life one year.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Empty containers may contain explosive gas.					